


# ULTRASHIP®-U2

## USER MANUAL



ENGLISH



Capacity  
0-1kg x 2g / 1-27kg x 5g

Thank you for purchasing the My Weigh® Ultra Ship®- U2 digital scale. Please read all operating instructions carefully before use. This electronic scale is a precision instrument. With normal care and proper treatment, it will provide years of reliable service. For more information please visit [www.myweigh.com](http://www.myweigh.com).

Never load the scale with more than the maximum capacity. Although the Ultra Ship®- U2 is designed to be extremely durable with extra overload protection built into the case, overloading will permanently damage it! Avoid any exposure to extreme heat or cold, your scale works better when operated at normal room temperature. Keep your scale in a clean environment. Dust, dirt, moisture, vibration, air currents and/or a close proximity to other electronic equipment can all cause an adverse effect on the reliability and accuracy of your scale. Handle with care. Gently apply all items to be weighed onto tray top. Avoid shaking, dropping or otherwise shocking the scale. Scales are delicate instruments and unlike cellular phones, scales have delicate sensors that determine how much an item weighs. If you drop or shock your scale, these sensors "feel" the shock and are sometimes destroyed. This happens with all digital scales. We design our scales to be as resistant to shock or drops as possible, however there is no way for us to protect 100% against load cell or sensor damage. Failure to follow these instructions will void your warranty.

Always allow the scale to acclimate to normal room temperature for at least one hour before use. Give your scale sufficient warm up time. Usually 30-60 seconds before calibration to give the internal components a chance to stabilize.

### PRECAUTIONS BEFORE USING THE BALANCE

1. Matter charged with static electricity can affect accuracy. Discharge all static electricity. For example, one method is to use Static-Guard spray, and spray it on both sides of the weighing platform.
2. The balance must be in an exactly horizontal position in order to achieve accurate measurement results.
3. Don't put any objects on the platform before powering on.
4. When possible please allow the scale to warm up for several minutes before operation.
5. Items should always be placed on the center of the platform when being weighed.
6. For optimum accuracy, recalibrate frequently.

### POWER SUPPLY

#### AC Adapter

The scale can be powered by an AC adapter - DC 5-9v 100mA. Please only use the correct AC adapter for this scale – an incorrect AC adapter can cause damage to the scale and possible fire or injury. Use of an incorrect AC adapter will also void your warranty.

## BATTERIES

---

Low Batteries & bad battery connections are the #1 cause of scale malfunction and inaccuracy! We test all of our scale returns from consumers and 60% of them are battery related problems. This sounds silly but it's true! A scale will perform poorly when it has low batteries. Use good quality batteries & replace them often (Remove the batteries if you plan to store the scale for longer than 14 days). We include good quality batteries with all of our scales but they can run low in storage. If your scale simply won't turn on while on battery power, it is often caused by loose battery connections. Battery prongs (terminals) are made of metal and they have to be in contact with the batteries. Some poorly designed batteries have recessed or partially obstructed battery terminals. This may cause your prongs to be touching the plastic housing of the battery instead of the metal of the battery terminal.

### Battery installation

- a) Press and lift open the battery cover located at the bottom of the unit.
- b) Insert the batteries and make sure the polarity is correct (+) and (-).
- c) Close the battery cover until it clicks shut.

Note : If the battery symbol appears in the display, it means low battery power. It is time to replace the battery.

## OPERATION INSTRUCTIONS

---

### Weighing Procedures

1. Press [**⓪**] to turn on the scale.

When the power is turned on, the scale will countdown for a few seconds and "0" will appear on the display.

2. The scale has TWO display lines - this means you can now read weights in two modes at the same time. Press [**M1**] or [**M2**] to toggle the weighing units g, kg, lb lb:oz, oz. To toggle the upper display mode press [**M1**] and the lower press [**M2**]. Once the unit has been selected, the selected unit will be displayed next to the weight value.

3. Start weighing

Verify the reading is "0". Place objects on the weighing platform to weigh. When the reading becomes stable, the stable indicator is displayed.

### TARE

Tare can be used for eliminating the weight value of an empty container. Place an empty container on the scale and press [**TARE**]. Then place the items to be weighed in the container. NOTE: When all weight is removed from the weighing tray, the tared value of a container will be displayed as a negative number. Press [**TARE**] again to return the scale to zero.

## CALIBRATION

---

Calibration may be required when the scale is first set up for use, or if the scale is moved to a different altitude or new location. This is necessary because the weight of a mass in one location is not necessarily the same in another location. Also, with time and use, mechanical deviations can occur.

### How to calibrate **\*\*you must have an accurate 20kg / 40lb weight or combination of weights in order to calibrate\*\***

1. From the off setting press & hold the [**M1**] button, then press the [**⓪**] button, release both keys. The display shows "CL. 20 kg" or "CL. 40lb".
2. Press [**M1**], to toggle the desired calibration weight "CL.40lb"=40lb or "CL.20kg"= 20kg and press [**M2**] to confirm.
3. The display will show "CAL". Place the correct calibration weight on the platform and then press [**TARE**]. The display will flash and show "PASS" when calibration is complete.
4. The calibration process is complete. The scale will return to normal weighing mode.

## SCALE FEATURES

### USB/ Software Connectivity

The U2 can be connected to most Windows® based computers using the the USB cable and by using our free software(activation V2.exe). You can download the latest version of this software at [www.myweigh.com/ultrasoftware](http://www.myweigh.com/ultrasoftware). If you close the activation window, communication will stop.

### Hold

Press the **[HOLD]** to hold the current weight reading, press **[HOLD]** again to cancel.

### Auto off

An auto shut off feature is provided to conserve battery power.


### To Enable or Disable the Auto-off

1. The scale should be OFF. Press and hold **[HOLD]** , then press and release **[ON]** the display will show "OFF 0"= Auto-Off disabled, "OFF 1"= Auto-off 2 minutes or "OFF 2" = Auto-Off 5minutes.
2. Press **[SEND]** to toggle between the auto off settings.
3. Press **[TARE]** to confirm the setting and return to weighing mode.


### Weighmeter®

On the side of the display you will notice a series of bars that increase as the load on the scale increases. This is our Weighmeter® invention. It helps you know the remaining capacity on the scale and also will indicate an overload if one occurs. Please use the Weighmeter® to monitor your weighing loads and please do not overload this scale.


## REMOVABLE DISPLAY OPERATION



- 1- Push the release button and slide the panel to the right



- 2- Pull the panel towards you



- 3- The display is separated and ready to use.

### DISPLAY SYMBOLS

	Hold Indicator
	Stability Indicator
	Scale is in TARE / ZERO mode
	Low Battery

### SPECIFICATIONS

<b>Capacity</b>	0-2lb/0-1kg 2-60lb/1-27kg	<b>Division</b>	2g/0.1oz 5g/0.2oz
<b>Units</b>	g, kg, lb, lb:oz, oz		
<b>Scale dimension</b>	240mm x 200mm x 50mm		
<b>Tray dimension</b>	170mm x 180mm		
<b>Operating temperature</b>	Optimum 10-40°C (50-104°F)		
<b>Power Source</b>	6 x AA batteries / DC 5-9v 100mA power adaptor or USB Adapter		
<b>Tare range</b>	Up to scale's maximum capacity		



[www.myweigh.com](http://www.myweigh.com)